

**CLAIMS:**

What is claimed is:

5

1. A three dimensional display, comprising:  
a three dimensional matrix of light emitting  
elements capable of generating images in three  
dimensions; and

10

a base coupled to the three dimensional matrix,  
the base having electrical circuitry for powering and  
controlling the three dimensional matrix.

15

2. The three dimensional display of claim 1, wherein  
the light emitting elements are pixels, and wherein each  
of the pixels has a red light emitting element, a green  
light emitting element, and a blue light emitting  
element.

20

3. The three dimensional display of claim 2, wherein  
the red light emitting element, green light emitting  
element and blue light emitting element are each  
comprised of a cell having an anode, a cathode, a gas  
volume and a phosphorus material.

25

4. The three dimensional display of claim 2, wherein  
the red light emitting element, green light emitting  
element, and blue light emitting element each have an  
anode and a cathode.

30

5. The three dimensional display of claim 2, wherein

009070-0252460

Sub  
C1

an anode of one of the pixels is shared by at least one other pixel.

6. The three dimensional display of claim 2, wherein a  
5 face of one of the pixels is shared by another pixel.

7. The three dimensional display of claim 2, wherein a  
top face of a pixel is the bottom face of a neighboring  
pixel, and wherein the side of the pixel is the side of  
10 another neighboring pixel.

8. The three dimensional display of claim 2, wherein  
electrical connections between the pixels, signal sources  
and power sources are positioned in seams between pixels.  
15

9. The three dimensional display of claim 2, wherein an  
anode bus line is positioned in a seam from a first anode  
of a pixel to a second anode of another pixel.

20 10. The three dimensional display of claim 2, wherein a  
first anode of a first red light emitting element of a  
pixel is connected to a second anode of a second red  
light emitting element in another pixel by a straight  
line bus connection along a seam in any direction in the  
25 three dimensional matrix.

11. The three dimensional display of claim 2, wherein a  
first anode of a first green light emitting element of a  
pixel is connected to a second anode of a second green  
30 light emitting element in another pixel by a straight  
line bus connection along a seam in any direction in the  
three dimensional matrix.

009070"04522460

12. The three dimensional display of claim 2, wherein a first anode of a first blue light emitting element of a pixel is connected to a second anode of a second blue light emitting element in another pixel by a straight line bus connection along a seam in any direction in the three dimensional matrix.
13. The three dimensional display of claim 2, wherein a first cathode of a first pixel is connected to a second cathode of a second pixel by a straight line connection along a seam in any direction in the three dimensional matrix.
14. The three dimensional display of claim 2, wherein the distance between two adjacent anodes is a square root of two multiplied by a length of one side of a pixel.
15. The three dimensional display of claim 10, wherein a distance between the first anode and the second anode of the first red light emitting element and the second red light emitting element is twice the length of one side of a pixel.
16. The three dimensional display of claim 13, wherein a distance between the first cathode and the second cathode of first pixel and the second pixel is twice the length of one side of a pixel.
17. The three dimensional display of claim 11, wherein the distance between the first anode and the second anode of the first green light emitting element and the second

0047750-010600

18. The three dimensional display of claim 12, wherein the distance between the first anode and the second anode of the first blue light emitting element and the second blue light emitting element is twice the length of one side of a pixel.

~~19. The three dimensional display of claim 1, further comprising a control system that controls which of the light emitting elements in the three dimensional matrix are illuminated.~~

20. The three dimensional display of claim 19, wherein the control system controls color, intensity and duration of the light emitted by the light emitting elements in the three dimensional matrix.

20 21. The three dimensional display of claim 19, wherein  
the control system receives an input image coded in a  
three dimensional coordinate system.

22. The three dimensional display of claim 21, wherein  
25 the input image is received from one of a computer,  
television signal receiver, cable system receiver,  
satellite receiver, and a storage medium.

23. The three dimensional display of claim 21, wherein  
30 the control system pixelizes the input image for  
reproduction by the three dimensional display.

[illegible]

Sub  
B2

Sub C<sup>15</sup>

Sub B3  
24. ~~The three dimensional display of claim 1, wherein the three dimensional matrix has a cube shape.~~

Sub a1  
5 25. A three dimensional display, comprising:  
a plurality of three dimensional light emitting elements configured to emit light in three dimensions; and  
a controller that controls the operation of the light emitting elements to generate a three dimensional  
10 image.

Sub B4  
15 26. ~~The three dimensional display of claim 25, wherein the light emitting elements are pixels, and wherein each of the pixels has a red light emitting element, a green light emitting element, and a blue light emitting element.~~

27. The three dimensional display of claim 26, wherein the red light emitting element, green light emitting  
20 element and blue light emitting element are each comprised of a cell having an anode, a cathode, a gas volume and a phosphorus material.

Sub 1  
25 28. The three dimensional display of claim 26, wherein a cathode of one of the pixels is shared by one or more other pixels.

29. The three dimensional display of claim 26, wherein the red light emitting element, green light emitting  
30 element, and blue light emitting element each have an anode and a cathode.

0093070-02522460

30. The three dimensional display of claim 26, wherein an anode of one of the pixels is shared by one or more other pixels.

5 31. The three dimensional display of claim 26, wherein a face of one of the pixels is shared by another pixel.

32. The three dimensional display of claim 26, wherein a top face of a pixel is the bottom face of a neighboring  
10 pixel, and wherein the side of a pixel is the side of another neighboring pixel.

33. The three dimensional display of claim 26, wherein electrical connections between the pixels, signal sources  
15 and power sources are positioned in seams between pixels.

34. The three dimensional display of claim 26, wherein an anode bus line is positioned in a seam from an anode  
20 of a pixel to an anode of another pixel.

35. The three dimensional display of claim 26, wherein a cathode line is positioned in a seam from a cathode of one pixel to a cathode of another pixel.

25 36. The three dimensional display of claim 26, wherein an anode of a red light emitting element of a pixel is connected to another anode of a red light emitting element in another pixel by a straight line bus connection along a seam in any direction.

30 37. The three dimensional display of claim 26, wherein an anode of a green light emitting element of a pixel is

009010"02522460

connected to another anode of a green light emitting element in another pixel by a straight line bus connection along a seam in any direction.

- 5 38. The three dimensional display of claim 26, wherein an anode of a blue light emitting element of a pixel is connected to another anode of a blue light emitting element in another pixel by a straight line bus connection along a seam in any direction.

10

39. The three dimensional display of claim 26, wherein a first cathode of a first pixel is connected to a second cathode of a second pixel by a straight line connection along a seam in any direction.

15

40. The three dimensional display of claim 26, wherein the distance between two adjacent anodes is the square root of two times the length of one side of a pixel.

20

41. The three dimensional display of claim 36, wherein the distance between the anodes of the red light emitting elements is twice the length of one side of a pixel.

25

42. The three dimensional display of claim 37, wherein the distance between the anodes of the green light emitting elements is twice the length of one side of a pixel.

30

43. The three dimensional display of claim 38, wherein the distance between the anodes of the blue light emitting elements is twice the length of one side of a pixel.

009010"0252460

44. The three dimensional display of claim 39, wherein the distance between the first cathode and the second cathode is twice the length of one side of a pixel.

5  
Sub B5  
45. ~~The three dimensional display of claim 25, wherein the controller controls the color, intensity and duration of the light emitted by the light emitting elements.~~

10 46. The three dimensional display of claim 25, wherein the controller receives an input image that is coded in a ~~three dimensional coordinate system.~~

15  
Sub C1  
47. The three dimensional display of claim 46, wherein the input image is received from one of a computer, television signal receiver, cable system receiver, satellite receiver, and a storage medium.

20 48. The three dimensional display of claim 46, wherein the control system pixelizes the input image for reproduction by the three dimensional display.

25  
Sub B6  
49. ~~The three dimensional display of claim 25, wherein the light emitting elements are formed into a matrix having a cube shape.~~

009070-0252450